# WIDE ROLL EYELETS



A choice of the most popular sizes in use for PC board and electronic assembly applications.




**MATERIAL:** Brass, Bright Electro Tin, MIL-T-10727. Other platings can be furnished.

| CAT. NO. | A OUTSIDE DIAMETER BARREL | B LENGTH UNDER FLANGE | C FLANGE DIAMETER | MTG. HOLE SIZE | STAKING TOOL CAT. NO. |
|---|---|---|---|---|---|
| 22 | .059 (1.49) O.D. .045 (1.14) I.D. | .062 (1.57) | .105 (2.7) | .062 (1.57) USE DRILL #51 | 3075 |
| 23 | | .093 (2.36) | | | |
| 24 | | .125 (3.18) | | | |
| 25 | | .156 (3.96) | | | |
| 26 | | .187 (4.75) | | | |
| 27 | | .219 (5.56) | | | |
| 33 | .089 (2.26) O.D. .070 (1.78) I.D. | .093 (2.36) | .150 (3.8) | .093 (2.36) USE DRILL #42 | 3076 |
| 34 | | .125 (3.18) | | | |
| 35 | | .156 (3.96) | | | |
| 36 | | .187 (4.75) | | | |
| 37 | | .219 (5.56) | | | |
| 43 | .121 (3.07) O.D. .102 (2.59) I.D. | .093 (2.36) | .200 (5.1) | .125 (3.18) USE DRILL #30 | 3077 |
| 44 | | .125 (3.18) | | | |
| 45 | | .156 (3.96) | | | |
| 46 | | .187 (4.75) | | | |
| 47 | | .219 (5.56) | | | |
| 48 | | .250 (6.35) | | | |
| 14 | .152 (3.86) O.D. .132 (3.35) I.D. | .125 (3.18) | .245 (6.2) | .156 (3.96) USE DRILL 5/32" | 3079 |
| 15 | | .156 (3.96) | | | |
| 16 | | .187 (4.75) | | | |
| 17 | | .219 (5.56) | | | |

**STAKING TOOLS**

Set consisting of top and bottom tool. Made from Tool Steel and highly polished.

TOP TOOL




BOTTOM TOOL

# SEMI-TUBULAR RIVETS

These standardized brass rivets typify the scope and variety of popular rivets that will provide faster and stronger assemblies at lower cost. We suggest you rivet and test a sample before purchasing large quantities for your application.




**MATERIAL:** Brass, Nickel Plate

| CAT. NO. | B LENGTH UNDER HEAD | A SHANK DIAMETER | H HEAD DIAMETER | MTG. HOLE SIZE |
|---|---|---|---|---|
| 3381 | .125 (3.2) | .060 (1.55) | .109 (2.8) | .067(1.70) Dia. USE DRILL #51 |
| 3382 | .156 (3.9) | | | |
| 3383 | .187 (4.8) | | | |
| 3384 | .156 (3.9) | .087 (2.21) | .147 (3.7) | .093 (2.36) Dia. USE DRILL #42 |
| 3385 | .187 (4.8) | | | |
| 3386 | .218 (5.5) | | | |
| 3387 | .250 (6.4) | | | |
| 3388 | .156 (3.9) | .120 (3.06) | .218 (5.5) | .128 (3.25) Dia. USE DRILL #30 |
| 3389 | .187 (4.8) | | | |
| 3390 | .218 (5.5) | | | |
| 3391 | .250 (6.4) | | | |

# SNAP RIVETS

Attach panels and mounting hardware without any tooling. Leaves a clean cosmetic look once installed. Can be installed without access to underside. Removable so assembly can be easily repaired or upgraded.




DWG. 1




DWG. 2




| CAT. NO. | DWG. | T PANEL THICKNESS | L RIVET LENGTH | D RIVET DIAMETER | A HEAD DIAMETER | B HEAD HEIGHT | MTG. HOLE SIZE |
|---|---|---|---|---|---|---|---|
| 3440 | 1 | .051/.079 (1.3/2.0) | .130 (3.3) | .076 (1.9) | .165 (4.2) | .047 (1.2) | .083/.087 (2.1/2.2) |
| 3441 | 1 | .083/.110 (2.1/2.8) | .160 (4.0) | | | | |
| 3442 | 1 | .114/.142 (2.9/3.6) | .190 (4.8) | | | | |
| 3443 | 2 | .118/.157 (3.0/4.0) | .220 (5.6) | .138 (3.5) | .252 (6.4) | .063 (1.6) | .142/.146 (3.6/3.7) |
| 3444 | 2 | .146/.181 (3.7/4.6) | .240 (6.1) | | | | |
| 3445 | 2 | .177/.217 (4.5/5.5) | .280 (7.1) | | | | |
| 3446 | 2 | .217/.256 (5.5/6.5) | .310 (7.9) | | | | |
| 3447 | 2 | .177/.217 (4.5/5.5) | .280 (7.1) | .158 (4.0) | .315 (8.0) | .071 (1.8) | .161/.165 (4.1/4.2) |
| 3448 | 2 | .217/.256 (5.5/6.5) | .310 (7.9) | | | | |
| 3449 | 2 | .256/.295 (6.5/7.5) | .350 (9.0) | | | | |
| 3450 | 2 | .295/.335 (7.5/8.5) | .390 (10.0) | | | | |

**MATERIAL:** Nylon 6/6, UL Rated 94V-2, Black



Tel (516) 328-7500 • Fax (516) 328-1080
(800) 221-5510 • kec@keyelco.com
KEYSTONE
RoHS COMPLIANT ~ ISO 9001 CERTIFIED
www.keyelco.com
55 S. Denton Avenue, New Hyde Park, NY 11040