



DATE	DESCRIPTION	REV.
6.27.19	CHANGE AS PER ECN 19-060 ROTATE TEST PINT IN THE POCKET FOR 90°	A
7.29.19	CHANGE AS PER ECN 19-062 INSULATION MAT'L WAS LCP 30% GLASS FILLED, UL 94V-0	B

PART NO.	BASE COLOR	PART NO.	BASE COLOR
5190TR	RED	5195TR	BROWN
5191TR	BLACK	5196TR	GREEN
5192TR	WHITE	5197TR	BLUE
5193TR	ORANGE	5198TR	GREY
5194TR	YELLOW	5199TR	PURPLE

NOTES:
 1. SUPPLIED ON TAPE AND REEL ONLY.
 TAPE AND REEL SPECIFICATIONS:
 2. TAPE:
 MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER
 ANSI/EIA-481 STANDARD
 3. REEL:
 7" [180.0] DIA. 1000 PIECES PER REEL

TEST POINT SPECIFICATIONS:
 1. CONTACT:
 MAT'L -.008 [0.20] THK PHOSPHOR BRONZE
 FINISH: SILVER PLATE
 2. INSULATOR:
 MAT'L -LCP, UL 94V-0
 (SEE COLOR IN THE TABLE)

THIS DOCUMENT IS THE PROPERTY OF KEYSTONE ELECTRONICS CORP. AND SHALL NOT BE REPRODUCED, DISTRIBUTED OR USED AS A BASIS FOR MANUFACTURE WITHOUT PRIOR WRITTEN PERMISSION FROM KEYSTONE ELECTRONICS CORP.

KEYSTONE ELECTRONICS CORP.
 www.keystone.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500

PART NAME: TEST POINT

MATERIAL: AS NOTED

FINISH: AS NOTED

TOLERANCES	INCH	[MM]	CODE	DWG NO.
DECIMAL	± .005	[± 0.13]	C	5190TR-5199TR
ANGULAR	± 1°			

DRN BY: NT DATE: 2.26.19
 App'D: LN SCALE: 5X