



DATE	DESCRIPTION	REV.
6.27.19	CHANGE AS PER ECN 19-060 ROTATE TEST PINT IN THE POCKET FOR 90°	A
7.29.19	CHANGE AS PER ECN 19-062 INSULATION MAT'L WAS LCP 30% GLASS FILLED, UL 94V-0	B

PART NO.	BASE COLOR	PART NO.	BASE COLOR
5190TR	RED	5195TR	BROWN
5191TR	BLACK	5196TR	GREEN
5192TR	WHITE	5197TR	BLUE
5193TR	ORANGE	5198TR	GREY
5194TR	YELLOW	5199TR	PURPLE

- NOTES:
- SUPPLIED ON TAPE AND REEL ONLY.
  - TAPE AND REEL SPECIFICATIONS:
  - TAPE:
    - MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER
    - ANSI/EIA-481 STANDARD
  - REEL:
    - 7" [180.0] DIA. 1000 PIECES PER REEL

- TEST POINT SPECIFICATIONS:
- CONTACT:
    - MAT'L -.008 [0.20] THK PHOSPHOR BRONZE
    - FINISH: SILVER PLATE
  - INSULATOR:
    - MAT'L -LCP, UL 94V-0
    - (SEE COLOR IN THE TABLE)

**KEYSTONE ELECTRONICS CORP.**  
 www.keystone.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500

PART NAME: TEST POINT  
 MATERIAL: AS NOTED  
 FINISH: AS NOTED

DRN BY: NT DATE: 2.26.19  
 App'D: LN SCALE: 5X

TOLERANCES INCH [MM]  
 DECIMAL ±.005 [± 0.13]  
 ANGULAR ± 1°  
 CODE: C DWG NO.: 5190TR-5199TR

THIS DOCUMENT IS THE PROPERTY OF KEYSTONE ELECTRONICS CORP. AND SHALL NOT BE REPRODUCED, DISTRIBUTED OR USED AS A BASIS FOR MANUFACTURE WITHOUT PRIOR WRITTEN PERMISSION FROM KEYSTONE ELECTRONICS CORP.