



DATE	DESCRIPTION	REV.
6.27.19	CHANGE AS PER ECN 19-060 ROTATE TEST PINT IN THE POCKET FOR 90°	A
7.29.19	CHANGE AS PER ECN 19-062 INSULATION MAT'L WAS LCP 30% GLASS FILLED, UL 94V-0	B

PART NO.	BASE COLOR	PART NO.	BASE COLOR
5190TR	RED	5195TR	BROWN
5191TR	BLACK	5196TR	GREEN
5192TR	WHITE	5197TR	BLUE
5193TR	ORANGE	5198TR	GREY
5194TR	YELLOW	5199TR	PURPLE

**KEYSTONE ELECTRONICS CORP.**

www.keystoneelectronics.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500

- NOTES:
- SUPPLIED ON TAPE AND REEL ONLY.
  - TAPE AND REEL SPECIFICATIONS:
  - TAPE:
    - MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER
    - ANSI/EIA-481 STANDARD
  - REEL:
    - 7" [180.0] DIA. 1000 PIECES PER REEL

- TEST POINT SPECIFICATIONS:
- CONTACT:
    - MAT'L -.008 [0.20] THK PHOSPHOR BRONZE
    - FINISH: SILVER PLATE
  - INSULATOR:
    - MAT'L -LCP, UL 94V-0
    - (SEE COLOR IN THE TABLE)

<b>KEYSTONE ELECTRONICS CORP.</b>			
www.keystoneelectronics.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500			
PART NAME			
TEST POINT			
MATERIAL			
AS NOTED			
FINISH		AS NOTED	
AS NOTED		AS NOTED	
TOLERANCES		CODE	
DECIMAL ± .005 [± 0.13 ]		DWG NO.	
ANGULAR ± 1°		C	
UNLESS OTHERWISE SPECIFIED		5190TR-5199TR	
DRN BY		DATE	
NT		2.26.19	
App'D		SCALE	
LN		5X	

THIS DOCUMENT IS THE PROPERTY OF KEYSTONE ELECTRONICS CORP. AND SHALL NOT BE REPRODUCED, DISTRIBUTED OR USED AS A BASIS FOR MANUFACTURE WITHOUT PRIOR WRITTEN PERMISSION FROM KEYSTONE ELECTRONICS CORP.