



DATE	DESCRIPTION	REV.
6.27.19	CHANGE AS PER ECN 19-060 ROTATE TEST PINT IN THE POCKET FOR 90°	A
7.29.19	CHANGE AS PER ECN 19-062 INSULATION MAT'L WAS LCP 30% GLASS FILLED, UL 94V-0	B

PART NO.	BASE COLOR	PART NO.	BASE COLOR
5190TR	RED	5195TR	BROWN
5191TR	BLACK	5196TR	GREEN
5192TR	WHITE	5197TR	BLUE
5193TR	ORANGE	5198TR	GREY
5194TR	YELLOW	5199TR	PURPLE

KEYSTONE ELECTRONICS CORP.

www.keystoneelectronics.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500

- NOTES:
- SUPPLIED ON TAPE AND REEL ONLY.
 - TAPE AND REEL SPECIFICATIONS:
 - TAPE:
 - MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER
 - ANSI/EIA-481 STANDARD
 - REEL:
 - 7" [180.0] DIA. 1000 PIECES PER REEL

- TEST POINT SPECIFICATIONS:
- CONTACT:
 - MAT'L -.008 [0.20] THK PHOSPHOR BRONZE
 - FINISH: SILVER PLATE
 - INSULATOR:
 - MAT'L -LCP, UL 94V-0
 - (SEE COLOR IN THE TABLE)

THIS DOCUMENT IS THE PROPERTY OF KEYSTONE ELECTRONICS CORP. AND SHALL NOT BE REPRODUCED, DISTRIBUTED OR USED AS A BASIS FOR MANUFACTURE WITHOUT PRIOR WRITTEN PERMISSION FROM KEYSTONE ELECTRONICS CORP.

<p>KEYSTONE ELECTRONICS CORP.</p> <p>www.keystoneelectronics.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500</p>			
PART NAME			
TEST POINT			
MATERIAL			
AS NOTED			
FINISH		AS NOTED	
AS NOTED		AS NOTED	
TOLERANCES	INCH	[MM]	CODE
DECIMAL	± .005	[± 0.13]	C
ANGULAR	± 1°		
UNLESS OTHERWISE SPECIFIED			
DRN BY	DATE	DWG NO.	
NT	2.26.19	5190TR-5199TR	
App'D	SCALE		
LN	5X		